

16 Channel Network DVR

TANDÉR®

2016 (with DVD-RW drive)



- Triplex operation with half D1 recording.
- Ready to take SATA HDD.
- High Resolution SXGA LCD monitor output.
- IR remote controller
- Friendly GUI with Mouse control.
- Easy archiving via USB pen drive or DVD-RW drive
- Remote LIVE view via IE or Mobile phone
- Made in Taiwan

- **User friendly remote control via network:** Users can enable remote monitoring, recording, playback control through IE browser and dedicated AP for easy operation.
- **Direct VGA output:** supports both 3:2 and 16:9 screen in ratio for up to 1280*1024 resolution.
- **Easy backup:** flexible to backup files through USB/ Remote site or DVD±RW.
- **Multi-layer authentication for maximum security.**
- **Triplex operation with MJPEG/MPEG4 compression:** high recording quality and fast network connection.
- **Unified and intuitive OSD/operation across all models:** shorten sales training and user learning.
- **Multiple and flexible operation control:** by mouse, IR controller and keypad operation.
- **S/W upgradable via USB pen drive:** enjoy latest feature by simply download new S/W from USB pen drive.
- **Supports SATA interface hard drive.**
- **Multi-lingual OSD supports.**
- **Supports PTZ control for PTZ camera.**
- **Quality product made in Taiwan**



Your DVR Solutions Start Here

TANDÉR®
CCTV . SINCE 1969

DVR 2016 Specification



S/W upgradable via USB pen drive.



DVD-RW for easy data backup.



IE browser supported for remote monitoring / recording / playback / PTZ control , 3G phone remote live view.



SXGA (1280 x 1024)

High Resolution output for LCD Monitor providing ultra clear image for Live display.

Model	2016
Video Format	NTSC/PAL
Video Compression	MJPEG
Internet Transmitting / Compression	MPEG4
Display Frame Rate	480/400fps
Recording Frame Rate (Auto balance)	120/100fps
Display Resolution	640x448/640x544
Recording Resolution	640x224/640x272
Display Division	Single/ Sequence/Split (1/4/8/16)
Video Input	BNCx16
Video Output	Video outx1, Spot monitor x1, S-Videox1, SXGAx1
Audio In/Out	1/1
Alarm In/Out	16/1
Recording Mode	Continuous/ Schedule / Motion Detection /Sensor
Recording Quality	High/Normal/Low
Search Mode	Time/Event
Storage	DVD-RW Drive X 1 + SATA HDDX2
Backup Device	USB stick /DVD±RW/CD-RW
Serial Connectors	USB 2.0x1, Mouse(Combo USB&PS/2 protocol)x1, RS485x1,
Network Connection	10/100 Ethernet(RJ-45)
Network Protocol	TCP/IP, Static IP, DHCP,PPPOE,DDNS(through Router)
Network Remote	Remote monitoring, recording, playback and PTZ by Client Program and IE browser. Support 3G Mobile phone remote viewing.
Power Supply	Input:AC100~240V 50/60 Hz,Output:DC12V 6.6A
Dimension(WxHxD)	430X80X320mm
Weight	6kg(W/O HDD)